




MiFare Electronic Cylinder



E-Cylinder with Mechanical Keys



Options



- >> Integrated within Omnitec's Gesthotel System to be used in conjunction with the Gaudi MiFare Lock
- >> Audit trail function saving the last 500 events

- >> Audit trail function saving the last 500 events

Product Features

- En1303 standard design which is easy to replace the traditional cylinders
- ★ Strictly encrypted communication which can't be duplicated, and the record can be tracked
- ★ Core part redundancy design could avoid damage of components
- ★ Module design and systematic management makes application, management and maintenance more convenient
- ★ The latest light sensing technology with acousto-optic reminding function, which free from the environmental impact
- ★ Apply multiple sensing and detection technology

- ★ Strictly encrypted communication which can't be duplicated, and the record can be tracked

- ★ Core part redundancy design could avoid damage of components

- ★ Module design and systematic management makes application, management and maintenance more convenient

- ★ The latest light sensing technology with acousto-optic reminding function, which free from the environmental impact

- ★ Apply multiple sensing and detection technology

Performance Parameters

- Working Power Supply: high performance 3.6V Li-SoCL2 Battery (ER14250 1/2 AA size)
- Battery Life: Maximum to 30000 door open operation, can operation another 100 times after the low voltage warning
- Applicable Key Cards: Mifare S50, reasonable adjustment for other card is available based on user requirement
- Working Temperature: -25 ~ +70℃
- Working Humidity: -20% ~ +97% R.H.
- Cylinder Dimensions: 60mm~ 100 mm (the minimum half-cylinder dimension is 30mm under non-equidistant situation)
- IP Grade : Internal(IP43), External(IP56)
- Certificate : CE, RoHS